



Scrubmaster® Latex Matte Interior Wall Finish

General Data

TYPICAL USES: On interior drywall, plaster, and masonry to provide the ultimate in scrubability and washability.

CHARACTERISTICS: Our best interior flat. Superior durability, scrubability, hiding and toughness. Stain resistant. Non-spatter technology. Good touch-up characteristics. This product meets the GS-11 Green Seal specification for low VOC paint. This product exceeds the LEED specification for low VOC paint. **Odor Free.**

COLORS AVAILABLE: White & over 1,200 custom colors.

APPLICATION: Synthetic brush, roller or airless spray.

RECOMMENDED PRIMERS:

Drywall: #120 Scrubmaster® Latex Drywall Primer

Plaster: #400 Ultra 100% Acrylic Supercoat Primer

New Wood: #960 Scott Seal Stain Block Primer or #400 Ultra 100% Acrylic Supercoat Primer

Concrete Block: #130 Allpro Interior Latex Block Filler

SPECIAL NOTES: Allow 30 days curing before washing or scrubbing. Warranted for Five Years, Material and Labor against wear-through due to excessive scrubbing. Do not apply to surfaces below 50°F. Exceeds Federal Specification #TT-P-29J.

MERCURY AND LEAD FREE FORMULA

Technical Data

FINISH: Matte Flat

VEHICLE TYPE: Proprietary Acrylic-Vinyl Blend

PAINT SOLIDS BY WEIGHT: 50.0%

PAINT SOLIDS BY VOLUME: 34.0%

VOC LEVEL: < 40 gms/ltr

VISCOSITY: 103 KU

COVERAGE: 300-400 square feet per gallon depending upon porosity and profile.

DRYING TIME AT 75°F/50% R.H.:

TOUCH: 45 Minutes

RECOAT: 2-3 Hours

SOLVENT: Water

CAUTION! Contains less than 10% Ethylene Glycol. May cause eye, skin, nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

KEEP OUT OF REACH OF CHILDREN

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.

SCOTT PAINT COMPANY

7839 Fruitville Rd • Sarasota, FL 34240 • 1-800-282-2016 • www.scottpaint.com