

**PRODUCT NAME: 210 SCRUBMASTER FLAT- WHITE**  
**PRODUCT CODE: 210W**

**HMIS CODES: H F R P**

===== **SECTION I - MANUFACTURER IDENTIFICATION** =====

MANUFACTURER'S NAME: Scott Paint Company  
 ADDRESS : 7839 Fruitville Road  
           Sarasota, FL 34240

EMERGENCY PHONE : 941-371-0015                      DATE PRINTED : 10/31/2007  
 INFORMATION PHONE : 941-371-0015                      NAME OF PREPARER : AARON NUTTER

===== **SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION** =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MM HG @ TEMP	WEIGHT PERCENT
-----			
TITANIUM DIOXIDE	13463-67-7		10.82
ACGIH TLV 10 Mg/m3 as Dust			
OSHA PEL 10 Mg/m3 Total Dust			
OSHA PEL 5 Mg/m3 Respirable Fraction			
TITANIUM DIOXIDE	13463-67-7		1.15
ACGIH TLV 10 Mg/m3 as Dust			
OSHA PEL 10 Mg/m3 Total Dust			
OSHA PEL 5 Mg/m3 Respirable Fraction			

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

===== **SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS** =====

BOILING RANGE: N/A    SPECIFIC GRAVITY (H2O=1): 1.3  
 VAPOR DENSITY: HEAVIER THAN AIR                              EVAPORATION RATE: SLOWER THAN ETHER  
 COATING V.O.C.: 47 g/l    MATERIAL V.O.C.: 17 g/l  
 SOLUBILITY IN WATER: INFINITELY SOLUBLE  
 APPEARANCE AND ODOR: VARIOUS COLORED LIQUID

===== **SECTION IV - FIRE AND EXPLOSION HAZARD DATA** =====

FLASH POINT: N/A    METHOD USED: N/A  
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A              UPPER: N/A

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

**SPECIAL FIREFIGHTING PROCEDURES**

FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, TO BE WORN. WATER SHOULD BE USED TO COOL CLOSED CONTAINERS TO PREVENT EXPLOSION DUE TO EXTREME HEAT.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== **SECTION V - REACTIVITY DATA** =====

**STABILITY:**  
**STABLE**

**CONDITIONS TO AVOID**

KEEP FROM FREEZING, EXTREME HEAT

**INCOMPATIBILITY (MATERIALS TO AVOID)**

NONE KNOWN.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

NONE KNOWN.

**HAZARDOUS POLYMERIZATION:**

WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

VAPOR OR SPRAY MIST COULD CAUSE HEADACHE, IRRITATION TO NOSE AND THROAT, DIZZINESS, WEAKNESS AND NAUSEA.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

EYE IRRITATION FROM VAPOR OR LIQUID.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

LIQUID IS NOT EASILY ABSORBED.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE-DIZZINESS, WEAKNESS, NAUSEA, HEADACHE,

CHRONIC-GASTROINTESTINAL IRRITATION.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No**

NONE KNOWN

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

NONE KNOWN

**EMERGENCY AND FIRST AID PROCEDURES**

INHALATION-REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT A PHYSICIAN.

EYE CONTACT-FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO PHYSICIAN FOR MEDICAL HELP.

SKIN CONTACT-WASH AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN FOR SKIN IRRITATION.

INGESTION-DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER

IMMEDIATELY, TREAT SYMPTOMATICALLY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

DIKE AND CONTAIN SPILL WITH INERT MATERIAL (SAND, SAWDUST ETC.). PUMP LIQUID INTO STORAGE TANKS, REMAINING LIQUID MAYBE TAKEN UP WITH INERT MATERIAL.

**WASTE DISPOSAL METHOD**

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

KEEP CONTAINER CLOSED AND UPRIGHT TO PREVENT LEAKAGE.

STORE BETWEEN 40F AND 100F.

**OTHER PRECAUTIONS**

DO NOT TAKE INTERNALLY.  
KEEP AWAY FROM CHILDREN.  
AVOID BREATHING VAPORS.

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. OTHERWISE USE NIOSH APPROVED RESPIRATOR DESIGNED TO REMOVE PARTICLES AN VAPOR.

**VENTILATION**

LOCAL EXHAUST NEEDED AT POINT OF RELEASE TO MAINTAIN EXPOSURE BELOW PEL OR TLV LEVELS.

**PROTECTIVE GLOVES**

RUBBER GLOVES FOR PROLONGED CONTACT.

**EYE PROTECTION**

CHEMICAL SPLASH GOGGLES RECOMMENDED TO AVOID EYE CONTACT.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

RUBBER APRON TO PROTECT CLOTHING FROM SPLASH DURING SPRAY APPLICATION.

**WORK/HYGIENIC PRACTICES**

WASH HANDS BEFORE EATING OR USING WASHROOM.

===== SECTION IX - DISCLAIMER =====

ALL INFORMATION, RECOMMENDATIONS AND SUGGESTIONS CONCERNING THIS PRODUCT ARE BASED UPON TESTS AND DATA BELIEVED TO BE RELIABLE. SCOTT PAINT COMPANY MAKES NO GUARANTEE, EXPRESSED OR IMPLIED, AS TO THE AFFECT OF USE, OR THE SAFETY AND TOXICITY OF THE PRODUCT. THE INFORMATION CONTAINED IN THIS SHEET IS NOT TO BE CONSTRUED AS ABSOLUTELY COMPLETE.

M A T E R I A L   S A F E T Y   D A T A   S H E E T

210 SCRUBMASTER FLAT WP-ACCENT

Page: 1

PRODUCT NAME: 210 SCRUBMASTER FLAT WP-ACCENT  
PRODUCT CODE: 210A

HMIS CODES: H F R P  
1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Scott Paint Company  
ADDRESS : 7839 Fruitville Road  
Sarasota, FL 34240

EMERGENCY PHONE : 941-371-0015      DATE PRINTED : 10/31/2007  
INFORMATION PHONE : 941-371-0015      NAME OF PREPARER : AARON NUTTER

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MM HG @ TEMP	WEIGHT PERCENT
HYDROUS MAGNESIUM SILICATE - DUST ONLY OSHA PEL: 20 MPP	14807-96-6	0.00000	68.00000 3.64

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: N/A      SPECIFIC GRAVITY (H2O=1): 1.22  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 33 g/l      MATERIAL V.O.C.: 11 g/l  
SOLUBILITY IN WATER: INFINITELY SOLUBLE  
APPEARANCE AND ODOR: VARIOUS COLORED LIQUID

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A      METHOD USED: N/A  
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A      UPPER: N/A

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

**SPECIAL FIREFIGHTING PROCEDURES**

FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, TO BE WORN. WATER SHOULD BE USED TO COOL CLOSED CONTAINERS TO PREVENT EXPLOSION DUE TO EXTREME HEAT.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== SECTION V - REACTIVITY DATA =====

**STABILITY:**  
STABLE

**CONDITIONS TO AVOID**  
KEEP FROM FREEZING, EXTREME HEAT

**INCOMPATIBILITY (MATERIALS TO AVOID)**  
NONE KNOWN.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

NONE KNOWN.

**HAZARDOUS POLYMERIZATION:**

**WILL NOT OCCUR.**

===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

VAPOR OR SPRAY MIST COULD CAUSE HEADACHE, IRRITATION TO NOSE AND THROAT, DIZZINESS, WEAKNESS AND NAUSEA.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

EYE IRRITATION FROM VAPOR OR LIQUID.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

LIQUID IS NOT EASILY ABSORBED.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE-DIZZINESS, WEAKNESS, NAUSEA, HEADACHE,

CHRONIC-GASTROINTESTINAL IRRITATION.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No**

NONE KNOWN

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

NONE KNOWN

**EMERGENCY AND FIRST AID PROCEDURES**

INHALATION-REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT A PHYSICIAN.

EYE CONTACT-FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO PHYSICIAN FOR MEDICAL HELP.

SKIN CONTACT-WASH AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN FOR SKIN IRRITATION.

INGESTION-DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER

IMMEDIATELY, TREAT SYMPTOMATICALLY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

DIKE AND CONTAIN SPILL WITH INERT MATERIAL (SAND, SAWDUST ETC.). PUMP LIQUID INTO STORAGE TANKS, REMAINING LIQUID MAYBE TAKEN UP WITH INERT MATERIAL.

**WASTE DISPOSAL METHOD**

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

KEEP CONTAINER CLOSED AND UPRIGHT TO PREVENT LEAKAGE.

STORE BETWEEN 40F AND 100F.

**OTHER PRECAUTIONS**

DO NOT TAKE INTERNALLY.

KEEP AWAY FROM CHILDREN.

AVOID BREATHING VAPORS.

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. OTHERWISE USE NIOSH APPROVED RESPIRATOR DESIGNED TO REMOVE PARTICLES AN VAPOR.

**VENTILATION**

LOCAL EXHAUST NEEDED AT POINT OF RELEASE TO MAINTAIN EXPOSURE BELOW PEL OR TLV LEVELS.

**PROTECTIVE GLOVES**

RUBBER GLOVES FOR PROLONGED CONTACT.

**EYE PROTECTION**

CHEMICAL SPLASH GOGGLES RECOMMENDED TO AVOID EYE CONTACT.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

RUBBER APRON TO PROTECT CLOTHING FROM SPLASH DURING SPRAY APPLICATION.

**WORK/HYGIENIC PRACTICES**

WASH HANDS BEFORE EATING OR USING WASHROOM.

===== SECTION IX - DISCLAIMER =====

ALL INFORMATION, RECOMMENDATIONS AND SUGGESTIONS CONCERNING THIS PRODUCT ARE BASED UPON TESTS AND DATA BELIEVED TO BE RELIABLE. SCOTT PAINT COMPANY MAKES NO GUARANTEE, EXPRESSED OR IMPLIED, AS TO THE AFFECT OF USE, OR THE SAFETY AND TOXICITY OF THE PRODUCT. THE INFORMATION CONTAINED IN THIS SHEET IS NOT TO BE CONSTRUED AS ABSOLUTELY COMPLETE.

M A T E R I A L   S A F E T Y   D A T A   S H E E T

210 SCRUBMASTER FLAT W P-TINT

Page: 1

PRODUCT NAME: 210 SCRUBMASTER FLAT W P-TINT
PRODUCT CODE: 210T

HMIS CODES: H F R P
0 0 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Scott Paint Company
ADDRESS : 7839 Fruitville Road
Sarasota, FL 34240

EMERGENCY PHONE : 941-371-0015 DATE PRINTED : 10/31/2007
INFORMATION PHONE : 941-371-0015 NAME OF PREPARER : AARON NUTTER

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE MM HG @ TEMP, WEIGHT PERCENT. Rows include TITANIUM DIOXIDE and HYDROUS MAGNESIUM SILICATE - DUST ONLY.

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.31
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 45 g/l MATERIAL V.O.C.: 15 g/l
SOLUBILITY IN WATER: INFINITELY SOLUBLE
APPEARANCE AND ODOR: VARIOUS COLORED LIQUID

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES
FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, TO BE WORN. WATER SHOULD BE USED TO COOL CLOSED CONTAINERS TO PREVENT EXPLOSION DUE TO EXTREME HEAT.

UNUSUAL FIRE AND EXPLOSION HAZARDS
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

SECTION V - REACTIVITY DATA

STABILITY:
STABLE

CONDITIONS TO AVOID

KEEP FROM FREEZING, EXTREME HEAT

**INCOMPATIBILITY (MATERIALS TO AVOID)**

NONE KNOWN.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

NONE KNOWN.

**HAZARDOUS POLYMERIZATION:**

**WILL NOT OCCUR.**

===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

VAPOR OR SPRAY MIST COULD CAUSE HEADACHE, IRRITATION TO NOSE AND THROAT, DIZZINESS, WEAKNESS AND NAUSEA.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

EYE IRRITATION FROM VAPOR OR LIQUID.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

LIQUID IS NOT EASILY ABSORBED.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE-DIZZINESS, WEAKNESS, NAUSEA, HEADACHE,

CHRONIC-GASTROINTESTINAL IRRITATION.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No**

NONE KNOWN

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

NONE KNOWN

**EMERGENCY AND FIRST AID PROCEDURES**

INHALATION-REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT A PHYSICIAN.

EYE CONTACT-FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO PHYSICIAN FOR MEDICAL HELP.

SKIN CONTACT-WASH AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN FOR SKIN IRRITATION.

INGESTION-DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER

IMMEDIATELY, TREAT SYMPTOMATICALLY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

DIKE AND CONTAIN SPILL WITH INERT MATERIAL (SAND, SAWDUST ETC.). PUMP LIQUID INTO STORAGE TANKS, REMAINING LIQUID MAYBE TAKEN UP WITH INERT MATERIAL.

**WASTE DISPOSAL METHOD**

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

KEEP CONTAINER CLOSED AND UPRIGHT TO PREVENT LEAKAGE.

STORE BETWEEN 40F AND 100F.

**OTHER PRECAUTIONS**

DO NOT TAKE INTERNALLY.  
KEEP AWAY FROM CHILDREN.  
AVOID BREATHING VAPORS.

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. OTHERWISE USE NIOSH APPROVED RESPIRATOR DESIGNED TO REMOVE PARTICLES AN VAPOR.

**VENTILATION**

LOCAL EXHAUST NEEDED AT POINT OF RELEASE TO MAINTAIN EXPOSURE BELOW PEL OR TLV LEVELS.

**PROTECTIVE GLOVES**

RUBBER GLOVES FOR PROLONGED CONTACT.

**EYE PROTECTION**

CHEMICAL SPLASH GOGGLES RECOMMENDED TO AVOID EYE CONTACT.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

RUBBER APRON TO PROTECT CLOTHING FROM SPLASH DURING SPRAY APPLICATION.

**WORK/HYGIENIC PRACTICES**

WASH HANDS BEFORE EATING OR USING WASHROOM.

===== SECTION IX - DISCLAIMER =====

ALL INFORMATION, RECOMMENDATIONS AND SUGGESTIONS CONCERNING THIS PRODUCT ARE BASED UPON TESTS AND DATA BELIEVED TO BE RELIABLE. SCOTT PAINT COMPANY MAKES NO GUARANTEE, EXPRESSED OR IMPLIED, AS TO THE AFFECT OF USE, OR THE SAFETY AND TOXICITY OF THE PRODUCT. THE INFORMATION CONTAINED IN THIS SHEET IS NOT TO BE CONSTRUED AS ABSOLUTELY COMPLETE.

M A T E R I A L   S A F E T Y   D A T A   S H E E T

210 SCRUBMASTER FLAT W P-DEEP

Page: 1

PRODUCT NAME: 210 SCRUBMASTER FLAT W P-DEEP  
PRODUCT CODE: 210D

HMIS CODES: H F R P  
0 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Scott Paint Company  
ADDRESS : 7839 Fruitville Road  
Sarasota, FL 34240

EMERGENCY PHONE : 941-371-0015      DATE PRINTED : 10/31/2007  
INFORMATION PHONE : 941-371-0015      NAME OF PREPARER : AARON NUTTER

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MM HG @ TEMP	WEIGHT PERCENT
TITANIUM DIOXIDE ACGIH TLV 10 Mg/m3 as Dust OSHA PEL 10 Mg/m3 Total Dust OSHA PEL 5 Mg/m3 Respirable Fraction	13463-67-7		6.22
HYDROUS MAGNESIUM SILICATE - DUST ONLY OSHA PEL: 20 MPP	14807-96-6	0.00000	68.00000 4.45
* ETHYLENE GLYCOL ACGIH TLV: 50 PPM	107-21-1	0.06	68.00 3

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 388 F      SPECIFIC GRAVITY (H2O=1): 1.28  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 116 g/l      MATERIAL V.O.C.: 42 g/l  
SOLUBILITY IN WATER: INFINITELY SOLUBLE  
APPEARANCE AND ODOR: VARIOUS COLORED LIQUID

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 241 F      METHOD USED: TCC  
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 3.2      UPPER: 15.3

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

**SPECIAL FIREFIGHTING PROCEDURES**

FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, TO BE WORN. WATER SHOULD BE USED TO COOL CLOSED CONTAINERS TO PREVENT EXPLOSION DUE TO EXTREME HEAT.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== SECTION V - REACTIVITY DATA =====

STABILITY:  
STABLE

**CONDITIONS TO AVOID**

KEEP FROM FREEZING, EXTREME HEAT

**INCOMPATIBILITY (MATERIALS TO AVOID)**

NONE KNOWN.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

NONE KNOWN.

**HAZARDOUS POLYMERIZATION:**

WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

VAPOR OR SPRAY MIST COULD CAUSE HEADACHE, IRRITATION TO NOSE AND THROAT, DIZZINESS, WEAKNESS AND NAUSEA.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

EYE IRRITATION FROM VAPOR OR LIQUID.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

LIQUID IS NOT EASILY ABSORBED.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE-DIZZINESS, WEAKNESS, NAUSEA, HEADACHE,

CHRONIC-GASTROINTESTINAL IRRITATION.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No**

NONE KNOWN

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

NONE KNOWN

**EMERGENCY AND FIRST AID PROCEDURES**

INHALATION-REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT A PHYSICIAN.

EYE CONTACT-FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO PHYSICIAN FOR MEDICAL HELP.

SKIN CONTACT-WASH AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN FOR SKIN IRRITATION.

INGESTION-DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER

IMMEDIATELY, TREAT SYMPTOMATICALLY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

DIKE AND CONTAIN SPILL WITH INERT MATERIAL (SAND, SAWDUST ETC.). PUMP LIQUID INTO STORAGE TANKS, REMAINING LIQUID MAYBE TAKEN UP WITH INERT MATERIAL.

**WASTE DISPOSAL METHOD**

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

KEEP CONTAINER CLOSED AND UPRIGHT TO PREVENT LEAKAGE.

STORE BETWEEN 40F AND 100F.

**OTHER PRECAUTIONS**

DO NOT TAKE INTERNALLY.  
KEEP AWAY FROM CHILDREN.  
AVOID BREATHING VAPORS.

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. OTHERWISE USE NIOSH APPROVED RESPIRATOR DESIGNED TO REMOVE PARTICLES AN VAPOR.

**VENTILATION**

LOCAL EXHAUST NEEDED AT POINT OF RELEASE TO MAINTAIN EXPOSURE BELOW PEL OR TLV LEVELS.

**PROTECTIVE GLOVES**

RUBBER GLOVES FOR PROLONGED CONTACT.

**EYE PROTECTION**

CHEMICAL SPLASH GOGGLES RECOMMENDED TO AVOID EYE CONTACT.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

RUBBER APRON TO PROTECT CLOTHING FROM SPLASH DURING SPRAY APPLICATION.

**WORK/HYGIENIC PRACTICES**

WASH HANDS BEFORE EATING OR USING WASHROOM.

===== SECTION IX - DISCLAIMER =====

ALL INFORMATION, RECOMMENDATIONS AND SUGGESTIONS CONCERNING THIS PRODUCT ARE BASED UPON TESTS AND DATA BELIEVED TO BE RELIABLE. SCOTT PAINT COMPANY MAKES NO GUARANTEE, EXPRESSED OR IMPLIED, AS TO THE AFFECT OF USE, OR THE SAFETY AND TOXICITY OF THE PRODUCT. THE INFORMATION CONTAINED IN THIS SHEET IS NOT TO BE CONSTRUED AS ABSOLUTELY COMPLETE.