



**Scrubmaster® Acrylic Latex Semi-Gloss Enamel**

**General Data**

**TYPICAL USES:** Interior walls and woodwork, concrete block, plaster, etc.

**CHARACTERISTICS:** Our best interior latex semi-gloss. Super adhesion over a variety of surfaces. Covers and flows very similar to alkyd enamels. Superior scrubability and durability. An excellent companion to Scrubmaster® Latex Wall Finishes. Non-yellowing. This product meets the GS-11 Green Seal specification for low VOC paint. This product exceeds the LEED specification for low VOC paint. **Odor Free.**

**COLORS AVAILABLE:** White and pastel colors.

**APPLICATION:** Synthetic brush, roller or airless spray.

**RECOMMENDED PRIMERS:**

**Drywall:** #120 Scrubmaster® Latex Drywall Primer

**Plaster:** #400 Ultra 100% Acrylic Supercoat Primer

**New Wood:** #400 Ultra 100% Acrylic Supercoat Primer or #960 Scott Seal Stain Block Primer

**Concrete Block:** #130 Allpro Latex Block Filler

**Old Gloss Alkyds:** #692 Aquaseal Latex Surface Conditioner White

**SPECIAL NOTES:** Do not apply to surfaces below 50°F. For best results use 2 coats. Meets Federal Specification #TT-P-1511. Allow 30 days curing before washing with strong cleaners. Warranted for five years, material and labor against wear through due to excessive scrubbing.

**MERCURY AND LEAD FREE FORMULA**

**Technical Data**

**FINISH:** Medium Semi-Gloss

**VEHICLE TYPE:** Proprietary 100% Acrylic-Vinyl Acrylic Blend

**PAINT SOLIDS BY WEIGHT:** 43.0%

**PAINT SOLIDS BY VOLUME:** 32.4%

**VOC LEVEL:** < 30 gms/ltr

**VISCOSITY:** 99 KU

**COVERAGE:** 300-400 square feet per gallon depending upon porosity and profile.

**DRYING TIME AT 75°F/50% R.H.:**

**TOUCH:** 1 Hour

**RECOAT:** 4 Hours

**SOLVENT:** Water

**CAUTION!** May cause eye, skin, nose and throat irritation.

**USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

**FIRST AID:** If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

**KEEP OUT OF REACH OF CHILDREN**

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

*It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.*

**SCOTT PAINT COMPANY**