



#400

Ultra 100% Acrylic Supercoat Primer

General Data

TYPICAL USES:

Priming new or bare wood and new plaster. Also excellent on stucco, masonry, aluminum and drywall.

CHARACTERISTICS:

Excellent covering, super adhering water based primer that has the ability to seal most tannin stains when properly used. Mildew and sulfide stain resistant. This product meets the GS-11 Green Seal specification for low VOC paint. This product exceeds the LEED specification for low VOC paint.

COLORS AVAILABLE: White.

APPLICATION: Synthetic brush, roller or airless spray.

RECOMMENDED PRIMERS:

In areas of exceptionally strong stain bleeding, use #510 Super-Seal Alkyd Exterior Primer.

SPECIAL NOTES:

Do not recoat for 12 hours for best stain blocking. Meets Green Seal GS-11 Specification. Do not apply to surfaces below 50°F.

MERCURY AND LEAD FREE FORMULA

Technical Data

FINISH: Very Low Sheen

VEHICLE TYPE: 100% Acrylic Emulsion

PAINT SOLIDS BY WEIGHT: 50.0%

PAINT SOLIDS BY VOLUME: 33.5%

VOC LEVEL: < 75 gms/ltr

VISCOSITY: 93-95 KU

WEIGHT PER GALLON: 11.04 lbs/gal

COVERAGE: 250-400 square feet per gallon depending upon porosity and profile.

DRYING TIME AT 75°F/50% R.H.:

TOUCH: 45 Minutes

RECOAT: 6 Hours (see notes)

SOLVENT: Water

CAUTION! Contains Zinc Oxide
May cause eye, skin, nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

KEEP OUT OF REACH OF CHILDREN

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.

SCOTT PAINT COMPANY

7839 Fruitville Rd • Sarasota, FL 34240 • 1-800-282-2016 • www.scottpaint.com