

M A T E R I A L S A F E T Y D A T A S H E E T

400W ACRYLIC SUPERCOAT PRIMER

Page: 1

PRODUCT NAME: 400W ACRYLIC SUPERCOAT PRIMER
PRODUCT CODE: 400W

HMIS CODES: H F R P
 1*0 0

===== **SECTION I - MANUFACTURER IDENTIFICATION** =====

MANUFACTURER'S NAME: Scott Paint Company
 ADDRESS : 7839 Fruitville Road
 Sarasota, FL 34240

EMERGENCY PHONE : 941-371-0015 DATE PRINTED : 10/31/2007
 INFORMATION PHONE : 941-371-0015 NAME OF PREPARER : AARON NUTTER

===== **SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION** =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MM HG @ TEMP	WEIGHT PERCENT
TITANIUM DIOXIDE ACGIH TLV 10 Mg/m3 as Dust OSHA PEL 10 Mg/m3 Total Dust OSHA PEL 5 Mg/m3 Respirable Fraction	13463-67-7		6.96
TEXANOL OSHA PEL: NOT EST. VOC 946GM/L	25265-77-4	0.01	68.00 1.85
TITANIUM DIOXIDE ACGIH TLV 10 Mg/m3 as Dust OSHA PEL 10 Mg/m3 Total Dust OSHA PEL 5 Mg/m3 Respirable Fraction	13463-67-7		1.58
* ZINC OXIDE - DUST ONLY OSHA PEL: 15MG/M3	1314-13-2	0.00000	68.00000 1

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

===== **SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS** =====

BOILING RANGE: 491 F SPECIFIC GRAVITY (H2O=1): 1.21
 VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
 COATING V.O.C.: 95 g/l MATERIAL V.O.C.: 36 g/l
 SOLUBILITY IN WATER: INFINITELY SOLUBLE
 APPEARANCE AND ODOR: VARIOUS COLORED LIQUID

===== **SECTION IV - FIRE AND EXPLOSION HAZARD DATA** =====

FLASH POINT: 248 F METHOD USED: TOC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.62 UPPER: 4.24

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES

FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, TO BE WORN. WATER SHOULD BE USED TO COOL CLOSED CONTAINERS TO PREVENT EXPLOSION DUE TO EXTREME HEAT.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====
SECTION V - REACTIVITY DATA
=====**STABILITY:**

STABLE

CONDITIONS TO AVOID

KEEP FROM FREEZING, EXTREME HEAT

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE KNOWN.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

NONE KNOWN.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

=====
SECTION VI - HEALTH HAZARD DATA
=====**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

VAPOR OR SPRAY MIST COULD CAUSE HEADACHE, IRRITATION TO NOSE AND THROAT, DIZZINESS, WEAKNESS AND NAUSEA.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE IRRITATION FROM VAPOR OR LIQUID.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

LIQUID IS NOT EASILY ABSORBED.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE-DIZZINESS, WEAKNESS, NAUSEA, HEADACHE,

CHRONIC-GASTROINTESTINAL IRRITATION.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

NONE KNOWN

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE KNOWN

EMERGENCY AND FIRST AID PROCEDURES

INHALATION-REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT A PHYSICIAN.

EYE CONTACT-FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO PHYSICIAN FOR MEDICAL HELP.

SKIN CONTACT-WASH AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN FOR SKIN IRRITATION.

INGESTION-DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER

IMMEDIATELY, TREAT SYMPTOMATICALLY.

=====
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
=====**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

DIKE AND CONTAIN SPILL WITH INERT MATERIAL (SAND, SAWDUST ETC.). PUMP LIQUID INTO STORAGE TANKS, REMAINING LIQUID MAYBE TAKEN UP WITH INERT MATERIAL.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINER CLOSED AND UPRIGHT TO PREVENT LEAKAGE.

STORE BETWEEN 40F AND 100F.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY.

KEEP AWAY FROM CHILDREN.

AVOID BREATHING VAPORS.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. OTHERWISE USE NIOSH APPROVED RESPIRATOR DESIGNED TO REMOVE PARTICLES AN VAPOR.

VENTILATION

LOCAL EXHAUST NEEDED AT POINT OF RELEASE TO MAINTAIN EXPOSURE BELOW PEL OR TLV LEVELS.

PROTECTIVE GLOVES

RUBBER GLOVES FOR PROLONGED CONTACT.

EYE PROTECTION

CHEMICAL SPLASH GOGGLES RECOMMENDED TO AVOID EYE CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

RUBBER APRON TO PROTECT CLOTHING FROM SPLASH DURING SPRAY APPLICATION.

WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE EATING OR USING WASHROOM.

===== SECTION IX - DISCLAIMER =====

ALL INFORMATION, RECOMMENDATIONS AND SUGGESTIONS CONCERNING THIS PRODUCT ARE BASED UPON TESTS AND DATA BELIEVED TO BE RELIABLE. SCOTT PAINT COMPANY MAKES NO GUARANTEE, EXPRESSED OR IMPLIED, AS TO THE AFFECT OF USE, OR THE SAFETY AND TOXICITY OF THE PRODUCT. THE INFORMATION CONTAINED IN THIS SHEET IS NOT TO BE CONSTRUED AS ABSOLUTELY COMPLETE.

M A T E R I A L S A F E T Y D A T A S H E E T

400UD ACRY PRIMER-ULTRA DEEP BASE

Page: 1

PRODUCT NAME: 400UD ACRY PRIMER-ULTRA DEEP BASE
PRODUCT CODE: 400UD

HMIS CODES: H F R P
1*0 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Scott Paint Company
ADDRESS : 7839 Fruitville Road
Sarasota, FL 34240

EMERGENCY PHONE : 941-371-0015 DATE PRINTED : 10/31/2007
INFORMATION PHONE : 941-371-0015 NAME OF PREPARER : AARON NUTTER

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE MM HG @ TEMP, WEIGHT PERCENT. Rows include TITANIUM DIOXIDE, ZINC OXIDE, and TEXANOL.

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 491 F SPECIFIC GRAVITY (H2O=1): 1.21
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 48 g/l MATERIAL V.O.C.: 19 g/l
SOLUBILITY IN WATER: INFINITELY SOLUBLE
APPEARANCE AND ODOR: VARIOUS COLORED LIQUID

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 248 F METHOD USED: TOC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.62 UPPER: 4.24
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES
FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, TO BE WORN. WATER SHOULD BE USED TO COOL CLOSED CONTAINERS TO PREVENT EXPLOSION DUE TO EXTREME HEAT.

UNUSUAL FIRE AND EXPLOSION HAZARDS
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

SECTION V - REACTIVITY DATA

STABILITY:

STABLE

CONDITIONS TO AVOID

KEEP FROM FREEZING, EXTREME HEAT

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE KNOWN.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

NONE KNOWN.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

VAPOR OR SPRAY MIST COULD CAUSE HEADACHE, IRRITATION TO NOSE AND THROAT, DIZZINESS, WEAKNESS AND NAUSEA.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE IRRITATION FROM VAPOR OR LIQUID.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

LIQUID IS NOT EASILY ABSORBED.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE-DIZZINESS, WEAKNESS, NAUSEA, HEADACHE,

CHRONIC-GASTROINTESTINAL IRRITATION.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

NONE KNOWN

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE KNOWN

EMERGENCY AND FIRST AID PROCEDURES

INHALATION-REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT A PHYSICIAN.

EYE CONTACT-FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO PHYSICIAN FOR MEDICAL HELP.

SKIN CONTACT-WASH AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN FOR SKIN IRRITATION.

INGESTION-DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER

IMMEDIATELY, TREAT SYMPTOMATICALLY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

DIKE AND CONTAIN SPILL WITH INERT MATERIAL (SAND, SAWDUST ETC.). PUMP LIQUID INTO STORAGE TANKS, REMAINING LIQUID MAYBE TAKEN UP WITH INERT MATERIAL.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINER CLOSED AND UPRIGHT TO PREVENT LEAKAGE.
STORE BETWEEN 40F AND 100F.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY.
KEEP AWAY FROM CHILDREN.
AVOID BREATHING VAPORS.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. OTHERWISE USE NIOSH APPROVED RESPIRATOR DESIGNED TO REMOVE PARTICLES AN VAPOR.

VENTILATION

LOCAL EXHAUST NEEDED AT POINT OF RELEASE TO MAINTAIN EXPOSURE BELOW PEL OR TLV LEVELS.

PROTECTIVE GLOVES

RUBBER GLOVES FOR PROLONGED CONTACT.

EYE PROTECTION

CHEMICAL SPLASH GOGGLES RECOMMENDED TO AVOID EYE CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

RUBBER APRON TO PROTECT CLOTHING FROM SPLASH DURING SPRAY APPLICATION.

WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE EATING OR USING WASHROOM.

===== SECTION IX - DISCLAIMER =====

ALL INFORMATION, RECOMMENDATIONS AND SUGGESTIONS CONCERNING THIS PRODUCT ARE BASED UPON TESTS AND DATA BELIEVED TO BE RELIABLE. SCOTT PAINT COMPANY MAKES NO GUARANTEE, EXPRESSED OR IMPLIED, AS TO THE AFFECT OF USE, OR THE SAFETY AND TOXICITY OF THE PRODUCT. THE INFORMATION CONTAINED IN THIS SHEET IS NOT TO BE CONSTRUED AS ABSOLUTELY COMPLETE.