



#402

Ultra 100% Acrylic Latex Block Filler

General Data

TYPICAL USES:

Priming and filling uncoated exterior and interior concrete block.

CHARACTERISTICS:

Heavy bodied, high solids coating allows easy application of thick coats to fill and smooth out pores. 100% Acrylic formulation resists efflorescence, fading, and peeling. Superior to conventional, cheap block fillers. This product meets the GS-11 Green Seal specification for low VOC paint. This product exceeds the LEED specification for low VOC paint.

COLORS AVAILABLE: White only.

APPLICATION: Synthetic brush, roller or airless spray.

RECOMMENDED PRIMERS:

N/A

SPECIAL NOTES:

Apply as many coats of Ultra Block Filler as necessary for proper pore filling. Do not apply to surfaces below 50°F and above 110°F. Surface temperature must be at least 5°F above dew point. Expect longer dry times at lower temperatures and higher relative humidity. Do not use on slick or smooth surfaces. As block surface porosity and pore size varies, predictability and consistency of surface smoothness is not guaranteed.

MERCURY AND LEAD FREE FORMULA

Technical Data

FINISH: Flat

VEHICLE TYPE: 100% Acrylic Emulsion

PAINT SOLIDS BY WEIGHT: 61.0 +/- 2%

PAINT SOLIDS BY VOLUME: 50.0 +/- 2%

VOC (THEORETICAL) AS SUPPLIED (UNTINTED):
< 75 gms/ltr

WEIGHT PER GALLON: 11.61 lbs.

WEIGHT PER GALLON: 12.40 lbs/gal

VISCOSITY: 136 +/- 2KU

THINNER: Do Not Thin

CLEAN-UP: Warm, Soapy Water

DRYING TIME AT 75°F/50% R.H.:

TOUCH: 1 Hour

RECOAT: 4 Hours

SPREAD RATE (THEORETICAL):

Rough Surface: 75 square feet per gallon

Smooth Surface: 150 square feet per gallon

Coverage does not include variations due to application methods or surface porosity.

RECOMMENDED APPLICATION THICKNESS: 50.0 mils WFT; 25.0 mils DFT

CAUTION!

May cause eye, skin, nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

KEEP OUT OF REACH OF CHILDREN

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.

SCOTT PAINT COMPANY

7839 Fruitville Rd • Sarasota, FL 34240 • 1-800-282-2016 • www.scottpaint.com