



#405

Ultra 100% Acrylic Stucco Primer

General Data

TYPICAL USES:

Priming new, bare stucco and vertical concrete.

CHARACTERISTICS:

Excellent covering, super adhering water based primer that has the ability to block excessive alkalinity and reduce efflorescence common in fresh stucco. This product meets the GS-11 Green Seal specification for low VOC paint. This product exceeds the LEED specification for low VOC paint.

Mildew and sulfide stain resistant.

COLORS AVAILABLE: White.

APPLICATION: Synthetic brush, roller or airless spray.

SPECIAL NOTES:

Do not use on chalky, old paint. For best results, pH of stucco surfaces should be 12 or less. Do not apply when air or surface temperature is below 50°F and above 110°F. Surface temperature must be at least 5°F above dew point. Expect longer dry times at lower temperatures and higher relative humidity.

Technical Data

FINISH: Low Sheen

VEHICLE TYPE: 100% Acrylic Emulsion

PERCENT SOLIDS BY WEIGHT: 47.5 +/- 2%

PERCENT SOLIDS BY VOLUME: 36.0 +/- 2%

VOC (THEORETICAL AS SUPPLIED, UNTINTED):
< 50 gms/ltr

WEIGHT PER GALLON: 10.92 lbs.

VISCOSITY: 100 KU

THINNER: Do Not Thin

CLEAN UP: Warm, Soapy Water

DRYING TIME AT 75°F/50% R.H.:

TOUCH: 1 Hour

RECOAT: 6 Hours

SPREAD RATE (THEORETICAL):

ROUGH SURFACE: 150 square feet per gallon

SMOOTH SURFACE: 350 square feet per gallon

Coverage does not include variations due to application methods or surface porosity.

RECOMMENDED APPLICATION THICKNESS: 5.5
Mils Wet; 2.0 Mils Dry

CAUTION! Contains Zinc Oxide and less than 10% Ethylene Glycol. May cause eye, skin, nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

KEEP OUT OF REACH OF CHILDREN

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.

SCOTT PAINT COMPANY

7839 Fruitville Rd • Sarasota, FL 34240 • 1-800-282-2016 • www.scottpaint.com