



TECHNICAL DATA SHEET

INTERIOR AND EXTERIOR LATEX PAINTS

#410

Ultra 100% Acrylic Flat Supercoat

General Data

TYPICAL USES: Most interior and exterior surfaces especially masonry, stucco, wood and properly primed non-ferrous metal.

CHARACTERISTICS: Our **BEST** quality exterior flat that is formulated for outstanding performance in the subtropical weather prevalent in Florida. Superior hiding, it applies easily with brush, roller or airless spray. Very durable. This product meets the GS-11 Green Seal specification for low VOC paint. This product exceeds the LEED specification for low VOC paint. Non-Yellowing. **Mildew, fade and sulfide stain resistant.**

COLORS AVAILABLE: White and unlimited custom colors.

APPLICATION: Synthetic brush, roller or airless spray.

RECOMMENDED PRIMERS:

Exterior Wood: #400 Ultra 100% Acrylic Supercoat Primer
Ferrous Metal: #941 Rust-Blok Alkyd Metal Primer/ #4000 Hydron Industrial Acrylic Metal Protective Primer
Aluminum and Galvanized Metal: #690 / #692 Aquaseal Late
Chalky Surfaces: #690/692 Aquaseal Latex Surface Conditioner
New Stucco and Masonry: #405 Ultra 100% Acrylic Stucco Primer
Concrete Block: #402 Ultra 100% Acrylic Latex Block Filler

SPECIAL NOTES: Do not apply when surface temperature is below 50°F. Woods prone to tannin stain bleeding may require one or more coats of Super Seal Alkyd Exterior Primer #510. Formulated to meet Green Seal GS-11 Specifications.

MERCURY AND LEAD FREE FORMULA

Technical Data

FINISH: Flat

VEHICLE TYPE: 100% Acrylic Emulsion

PAINT SOLIDS BY WEIGHT: 53.0% ±1%

PAINT SOLIDS BY VOLUME: 40.0% ±1%

VOC (THEORETICAL)

AS SUPPLIED (UNTINTED): < 50 gms/ltr

WEIGHT PER GALLON: 10.9 lbs./ gal.

VISCOSITY: 103 ± 2 KU

THINNER: If necessary, thin with clean water up to 1/2 pint per gallon

CLEAN UP: Warm, Soapy Water

DRYING TIME AT 75°F/50% R.H.:

TOUCH: 30 Minutes

RECOAT: 2-4 Hours

SPREAD RATE (THEORETICAL):

Rough Surface: 150-200 sq. ft. / gal

Smooth Surface: 300-400 sq. ft. / gal

Coverage does not include variations due to application methods or surface porosity.

RECOMMENDED APPLICATION THICKNESS:

5.0 mils Wet Film Thickness, 2.0 mils Dry Film Thickness

LIMITS OF PRODUCT USAGE: Do not apply when air or surface temperature is below 50°F and above 110°F. Surface temperature must be at least 5°F above dew point. Expect longer dry times at lower temperatures and higher relative humidity

CAUTION!

Contains Zinc Oxide.

May cause eye, skin, nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

KEEP OUT OF REACH OF CHILDREN

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.

SCOTT PAINT COMPANY

7839 Fruitville Rd • Sarasota, FL 34240 • 1-800-282-2016 • www.scottpaint.com

11/11