



TECHNICAL DATA SHEET INTERIOR AND EXTERIOR LATEX PAINTS

#425

Allgrip Acrylic Satin Enamel

General Data

TYPICAL USES: As a heavy duty recoat paint over old alkyd, epoxy and latex paints especially on hospital and school walls and trim where proper surface preparation is difficult. Also excellent on properly primed wood, masonry, drywall, plaster and metals. Interior and exterior.

CHARACTERISTICS: Our **super premium**, high adhesion acrylic satin enamel. Applies like and dries almost as hard as oil based enamels. It has superior adhesion to old, hard enamels. Excellent for interior walls and trim. Extremely durable and cleanable with a variety of heavy duty cleaners. Low odor, non-yellowing. This product meets the GS-11 Green Seal specification for low VOC paint. This product exceeds the LEED specification for low VOC paint. **Mildew and fade resistant.***
Non-toxic.

COLORS AVAILABLE: White and unlimited custom colors

APPLICATION: Synthetic brush, roller or airless spray.

RECOMMENDED PRIMERS:

Interior Wood: #400 Ultra 100% Acrylic Supercoat Primer or #960 Seal N'Hide Fast Dry Stain Block Primer

Exterior Wood: #400 Ultra 100% Acrylic Supercoat Primer or #510 Super-Seal Alkyd Exterior Primer

Drywall: #400 Ultra 100% Acrylic Supercoat Primer or #120 Scrubmaster Latex Drywall Primer

Ferrous Metal: #941 Rust-Blok Alkyd Metal Primer, #931 Encapsulon Surface Tolerant Epoxy Mastic Primer or #4000 Hydron Industrial Acrylic Metal Protective Primer

Aluminum and Galvanized Metal: #692 Aquaseal Latex Surface Conditioner

Chalky Surfaces: #690/692 Aquaseal Latex Surface Conditioner

Old Enamels: Thoroughly clean and degrease

Stucco: #405 Ultra 100% Acrylic Stucco Primer

Plaster: #400 Ultra 100% Acrylic Supercoat Primer

SPECIAL NOTES: Exceeds Fed. Spec. #TT-P-960. Woods prone to tannin stain bleeding may require one or more coats of Super-Seal Alkyd Exterior Primer #510. **MERCURY AND LEAD FREE FORMULA**

Technical Data

FINISH: Satin

VEHICLE TYPE: Acrylic Emulsion

PAINT SOLIDS BY WEIGHT: 46.0% ±1%

PAINT SOLIDS BY VOLUME: 32.0% ±1%

VOC (THEORETICAL)

AS SUPPLIED (UNTINTED): < 150 gms/ltr

WEIGHT PER GALLON:

VISCOSITY: 10.7

THINNER: If necessary, thin with clean water up to 1/2 pint per gallon

CLEAN UP: Warm, Soapy Water

DRYING TIME AT 75°F/50% R.H.:

TOUCH: 30 Minutes

RECOAT: 2-4 Hours

SPREAD RATE (THEORETICAL):

Rough Surface: 150-200 sq. ft. / gal

Smooth Surface: 300-400 sq. ft. / gal

Coverage does not include variations due to application methods or surface porosity.

RECOMMENDED APPLICATION THICKNESS:

6.0 mils Wet Film Thickness, 2.0 mils Dry Film Thickness

LIMITS OF PRODUCT USAGE: Do not apply when air or surface temperature is below 50°F and above 110°F. Surface temperature must be at least 5°F above dew point. Expect longer dry times at lower temperatures and higher relative humidity

CAUTION!

May cause eye, skin, nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

KEEP OUT OF REACH OF CHILDREN

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.

SCOTT PAINT COMPANY

7839 Fruitville Rd • Sarasota, FL 34240 • 1-800-282-2016 • www.scottpaint.com

10/11