



TECHNICAL DATA SHEET EXTERIOR LATEX PAINTS

#430

Ultra 100% Acrylic Semi-Gloss Supercoat

General Data

TYPICAL USES: Most interior and exterior surfaces of wood, masonry, stucco, galvanized steel, aluminum, fiberglass, properly primed ferrous metal, composition and fiber cement board.

CHARACTERISTICS: Our **BEST** quality exterior semi-gloss that is formulated for top performance in the sub-tropical weather prevalent in Florida. It contains the best in pigments, resins and fungicides to impart superior resistance to moisture and sunlight. Super hiding and very scrubbable. Non-yellowing. Five Year Limited Mildew Warranty. Product is treated with fungicides to resist the growth of mildew on the product film. This product meets the GS-11 Green Seal specification for low VOC paint. This product exceeds the LEED specification for low VOC paint.

COLORS AVAILABLE: White, black and unlimited custom colors.

APPLICATION: Synthetic brush, roller or airless spray.

RECOMMENDED PRIMERS:

Wood: #400 Ultra 100% Acrylic Supercoat Primer

Drywall: #120 Scrubmaster Latex Drywall Primer

Ferrous Metal: #941 Rust-Blok Alkyd Metal Primer / #4000 Hydron

Aluminum and Galvanized Metal: #400 Ultra 100% Acrylic Supercoat Primer

Slightly Rusted Metal: #931 Encapsulon Epoxy Surface Tolerant Mastic Primer

Chalky Surfaces: #690/692 Aquaseal Latex Surface Conditioner

New Stucco and Masonry: #405 Ultra 100% Acrylic Stucco Primer

Fiber cement Board: #400 Ultra 100% Acrylic Supercoat Primer

SPECIAL NOTES: Do not apply when surface temperature is below 50°F. Meets Green Seal GS-11 specifications. Woods prone to tannin stain bleeding may require one or more coats of Super Seal Alkyd Exterior Primer #510.

MERCURY AND LEAD FREE FORMULA

Technical Data

FINISH: Semi-Gloss

VEHICLE TYPE: 100% Acrylic Emulsion

PAINT SOLIDS BY WEIGHT: 42.0% ±1%

PAINT SOLIDS BY VOLUME: 35.0% ±1%

VOC (THEORETICAL)

AS SUPPLIED (UNTINTED): < 100 gms/ltr

WEIGHT PER GALLON: 9.8

VISCOSITY: 102 ± 2 KU

THINNER: If necessary, thin with clean water up to 1/2 pint per gallon

CLEAN UP: Warm, Soapy Water

DRYING TIME AT 75°F/50% R.H.:

TOUCH: 1 Hour

RECOAT: 4 Hours

SPREAD RATE (THEORETICAL):

Rough Surface: 150-200 sq. ft. / gal

Smooth Surface: 300-400 sq. ft. / gal

Coverage does not include variations due to application methods or surface porosity.

RECOMMENDED APPLICATION THICKNESS:

6.0 mils Wet Film Thickness, 2.0 mils Dry Film Thickness

LIMITS OF PRODUCT USAGE: Do not apply when air or surface temperature is below 50°F and above 110°F. Surface temperature must be at least 5°F above dew point. Expect longer dry times at lower temperatures and higher relative humidity

CAUTION!

May cause eye, skin, nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

KEEP OUT OF REACH OF CHILDREN

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.

SCOTT PAINT COMPANY

7839 Fruitville Rd • Sarasota, FL 34240 • 1-800-282-2016 • www.scottpaint.com 10/11